

## A versatile solution for automotive accessories.

- Quick and easy, one-step assembly!
- Made with 21-gauge braided stainless steel wire for extraordinary strength.
- Self-locking mechanism and EAS label hidden in body of tag.
- Thin poly-coated wire construction allows for easy insertion into the smallest openings without scratching.
- Touch or proximity deactivated.
- Barcode labels may be ordered online through our Mabel Service Bureau.
- All Sensormatic certified solutions.



Plastic coated wire cable prevents scratching of product.



### SELF-LOCKING TAG

before assembly



Thin self-locking wire.

Sensormatic label is completely enclosed in hard plastic casing which cannot be bent or twisted.

after assembly



End of wire is enclosed in body of tag. No sharp edges exposed or excess wire to cut off after assembly.



Noose design  
Style# EAS-SL01



Continuous Loop design  
Style# EAS-SL02

### SALES CONTACTS & ORDERING INFORMATION

Patent Pending



**A&H, USA**  
T 401-943-5040  
F 401-942-1160  
E sales@aandhusa.com

**A&H, EUROPE**  
T 44-1403-710055  
F 44-1403-711082  
E sales@aandheurope.com

**A&H, CANADA**  
T 416-498-8822  
F 416-498-0485  
E sales@aandhcanada.com

**A&H, ASIA**  
T 86-769-516-6000  
F 86-769-516-9800  
E ahtaiping@aandhasia.net